



## Seismic™ 110

Amplifier High Current Discrete Output	1,700 watts Dynamic Peak / 850 watts RMS Sustained
Amplifier Design Features	Auto-On/Off, Trigger-On/Off, soft clipping, thermal protection, electrical shorting protection
Subwoofer Bass Driver	high-temperature Apical™ formers, dual 12-mm-thick top plates, 10-lb (4.5 kg) triple ceramic (hard ferrite) magnet structure, 38-mm (1-1/2 in) diameter split voice-coil construction (60-mm coil lengths), inverted Santoprene® surround, dual Nomex® spiders, 254-mm (10 in) high-excursion mineral-filled co-polymer polypropylene cone with RCR™ resonance-control ribbing on underside, FEA-optimized overmolded, AVS™ die-cast heatsink chassis
Low Frequency Extension	18 Hz (DIN)
Subwoofer Cutoff Frequency	Variable 35 Hz - 150 Hz; Bypass option
Sub./Sat. Phase Alignment	Variable 0° - 180°
Line Level Input	RCA (S/E) Left and Right or Sub-Out / LFE or Balanced XLR. From Sub-Out / LFE-Out of preamp/processor or other line-level source
Line Level Input Impedance	RCA:10k ohms; XLR:20k ohms
Line Level Input Sensitivity	100 mV Mono
Accessory	Paradigm Perfect Bass Kit™ (sold sep.)

Height,Width,Depth	34.3 cm x 29.8 cm x 32 cm
	13-1/2 in x 11-3/4 in x 12-5/8 in
Weight	37lb / 16.80kg
Finishes	Satin Black